



Bobcat®

Planer

Attachments



Benefits

Equipped with direct-drive, high-torque hydraulic motors, these low maintenance attachments efficiently mill asphalt or concrete. The planers feature hydraulic side-shift for planing close to walls and curbs. Consistent depth control and ski depth visible from the operator seat. Make precise adjustments with fingertip controls.

Applications

- Construction
- Road repairs

Approved machines

| | 14" / 36 cm Standard-Flow Planer | 18" / 45 cm High-Flow Planer | 24" / 61 cm High-Flow Planer | 40" / 100 cm High-Flow Planer | 16" / 41 cm Surface Planer |
|-----------------------|--|---|---|--|---|
| Approved for loaders: | S130, S150, S160, S175, S185, S205, S220, S250, S300, A300, T140, T190, T250, T300 | S160H, S175H, S185H, S205H, S220H, S250H, S300H, A300H, T190H, T250H, T300H | S160H, S175H, S185H, S205H, S220H, S250H, S300H, A300H, T190H, T250H, T300H | S220H, S250H, S300H, A300H, T250H, T300H | S160H, S175H, S185H, S205H, S220H, S250H, S300H, A300H, T190H, T250H, T300H |

Weights and dimensions

| | 14" / 36 cm Standard-Flow Planer | 18" / 45 cm High-Flow Planer | 24" / 61 cm High-Flow Planer | 40" / 100 cm High-Flow Planer | 16" / 41 cm Surface Planer |
|-----------------------|-------------------------------------|---------------------------------|---------------------------------|----------------------------------|-------------------------------|
| Operating weight (kg) | 662 | 701 | 805 | 1043 | 723 |
| Overall width (mm) | 1651 | 1651 | 1651 | 1727 | 1651 |
| Overall height (mm) | 711 | 711 | 711 | 813 | 711 |
| Overall length (mm) | 1278 | 1278 | 1278 | 1118 | 1278 |

Performance

| | 14" / 36 cm Standard-Flow Planer | 18" / 45 cm High-Flow Planer | 24" / 61 cm High-Flow Planer | 40" / 100 cm High-Flow Planer | 16" / 41 cm Surface Planer |
|------------------------------------|-------------------------------------|---------------------------------|---------------------------------|----------------------------------|-------------------------------|
| Cutting width (with std drum) (mm) | 356 | 457 | 610 | 1016 | 406 |
| Cutting depth (with std drum) (mm) | 0 – 152 | 0 – 152 | 0 – 152 | 0 – 130 | 0 – 152 |
| Max. oscillation angle (°) | ± 15 | ± 15 | ± 15 | ± 8 | ± 15 |
| Side-shift (mm) | 660 | 660 | 660 | 650 | 660 |
| Planing distance next to curb (mm) | flush | flush | flush | 65 | flush |

